

June, 2017

3M™ Laser Markable Label Material 7847

Product Description

3M™ Laser Markable Label Material 7847 are specialty film label materials where a laser can ablate the top layer of a dual-layer facestock to create an image. The same laser can also kiss cut the label to size, maximizing flexibility for producing variable labels for durable applications.



Product Features

- Cast modified acrylate facestock offers long-term durability and excellent abrasion, temperature, chemical and environmental resistance
- High-resolution and high-contrast images markable with standard Nd-Yag lasers for smaller barcodes, 2-D symbologies and fine point text.
- Excellent convertability (“kiss cutting”) of acrylate facestock on densified kraft liner.
- Matte surface provides good printability resulting in excellent bar code readability.
- 3M™ High Performance Acrylic Adhesive 350 provides reliable, permanent adhesion to LSE plastics, oily metals, powder coatings and textured surfaces.
- Brittle facestock material provides destructibility to meet security labeling requirements.
- No corrosive emissions during the laser marking process.
- UL Recognized Component under file MH11410.
- CSA Recognized Component under file 99316.

3M™ Laser Markable Label Material 7847

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values	
Facestock Thickness	0.06 mm	2.4 mil
Adhesive	#350 high-holding acrylic	
Adhesive Thickness	0.03 mm	1.2 mil
Liner	Densified Kraft	
Liner Thickness	0.077 mm	3.0 mil

Note

Calipers are nominal values

Typical Performance Characteristics

Property	Values	
Tensile Strength	28 N/cm	3.1 oz/in
Elongation at Break	ca. 5 %	
Minimum Application Temperature	4 °C	39 °F

3M™ Laser Markable Label Material 7847

Environmental Performance

Note: The following tests are intended as a guide to product performance. Application testing is recommended using actual substrates, expected dwell times, and actual conditioning for best determination of product suitability.
Temperature Resistance: Resistant up to 392°F (200°C) (when applied to aluminum surfaces) 440°F (225°C) for 60 min

Dimensional Stability: <1% after 2 hours at 200 °C, or 24 hours at 150 °C
<1% after 24 hours -40°C:

Adhesive Performance/Bond Strength:

Substrate	Oz/in	N/in
Stainless Steel	115	32
Polypropylene	86	24
Polycarbonate	82	23
ABS	93	26

72 hour room temperature dwell, 300 mm/min, at 180° angle, film width: 25.4 mm. Adhesive performance for each case can depend on the texture of the surface. The above adhesive values are average values. They are not appropriate for specifications.

Weather Resistance: Acceleration test in the Xenon device, 2000 hours: No change.

Resistance to Environmental Conditions:

(applied to aluminum): No change.

24 hours: -40°F (-40°C)

24 hours: 300°F (150°C)

2 hours: 390°F (200°C)

Resistance to Chemical Immersion:

Substance	Exposure	Time Results
Diesel	4 hours	No change
Dot 4	1 hour	No change

Salt Spray: 150 Hours : no change

Processing

Laser Marking:

- 3M™ Laser Markable Label Material 7847 are compatible with many kinds of dispenser systems and is suitable for a continuous process with minimal supervision.
- 3M recommends operating an exhaust system combined with a charcoal filter to reduce emissions during the laser operation.
- All Nd-Yag laser marking equipment on the market can ablate and “kiss cut” 3M™ Laser Markable Label Material 7847.
- For optimized optical results, 3M recommends individually adjusting marking parameter, such as power, pulse rate, and speed, to your individual requirements depending on the type of labels to be produced (bar codes or characters).

Printing:

- When using press printing methods, 3M recommends pre-printing tests to check for sufficient ink adhesion.

3M™ Laser Markable Label Material 7847

Handling/Application Information

Application Ideas

- Durable goods marking
- Under hood labels
- Barcode labels
- Process labeling in-plant
- Asset labels
- Security labels
- Information labels with 2-D symbologies

Storage and Shelf Life

Store at room temperature conditions in cool, dry and sun-protected rooms.

If stored under proper conditions, product retains its performance and properties for 24 months from date of manufacture.

Industry Specifications

UL Recognized (File MH11410)

CSA Accepted (File 99316)

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-Laser-Markable-Label-Stock/?N=5002385+3291133795&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=7847

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Laser Markable Label Material 7847

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M™ Laser Markable Label Material 7847



Industrial Adhesives and Tapes
Division
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2020. All Rights
Reserved.

The brands listed above are trademarks of
3M