

tesa® 4651

Premium Acrylic Coated Colored Cloth Tape

tesa® 4651 is a robust, high-quality, acrylic coated cloth tape. It is based on a 145 mesh woven rayon fabric backing and a natural rubber adhesive. The cloth tape is conformable and features excellent abrasion resistance, high tensile strength, as well as a very high adhesiveness to multiple, even rough surfaces. The tape's high tack and short dwell time ensure a fast application and reliable adhesion only shortly after having been applied. The tape is hand-tearable and can be torn with precise and straight edges longitudinally and horizontally. tesa® 4651 offers exceptionally high abrasion resistance, water resistance, and can withstand temperatures of up to 130°C for short term after which it can be removed without residues. Strong cloth tape tesa® 4651 is usable for a wide range of applications in various industries. Black and blue is also available with paper liner as jumbo roll (tesa® 4651 PV9).

Main Application

- Masking while sandblasting, coating, paint spraying, etc.
- Bundling and reinforcing of freight, such as pipes or profiles
- Labeling, color coding or marking of wires, cables, etc
- Permanent sealing of pipe joints, tins and tubes
- Securing of sharp edges
- Fixing and insulating of wires

Technical Data

▪ Backing material	acrylic-coated cloth	▪ Elongation at break	13 %
▪ Total thickness	310 µm	▪ Tensile strength	100 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance (30 min)	130 °C
▪ Adhesion to steel	3.3 N/cm	▪ Mesh	145 count per square inch

Properties

▪ Hand tearability	●●●●	▪ Suitable for die cutting	yes
▪ Straight tear edges	●●●●	▪ Abrasion resistance	●●●●
▪ Easy to write on	yes	▪ Water resistance	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Complies with LV 312-1 Dielectric strength.

For latest information on this product please visit <http://l.tesa.com/?ip=04651>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.