productinformation

tesa® 53315

Non-staining medium strength mono filament tape

tesa® 53315 is a medium strength polyester backed fiberglass reinforced filament tape.

tesa® 53315 has a high tack and good shear resistant adhesive system. It has very good aging properties and assures clean removal from many substrates. It is also non-staining.

Main Application

- Transport securing of appliances and office automation equipment
- Securing and stabilizing of furniture for transportation
- Securing of thin metal coils for end-tabbing
- Bundling of medium weight goods, e.g. plastic pipes, flooring materials

Technical Data

Backing material	glassfibre / PET film	Adhesion to steel	7 N/cm
Total thickness	140 µm	Elongation at break below	5 %
Type of adhesive	synthetic rubber	Tensile strength	380 N/cm

Properties

Residue free removal	yes

For latest information on this product please visit http://l.tesa.com/?ip=53315

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

great to work with